

Product datasheet

Specifications



Easy UPS 3S Pro 15 kVA 400V 3:3
UPS, 2 internal 7Ah modular battery
strings, expandable to 3

E3SP15KHB2

Main

Main input voltage	3 phases
Input current	(3 phases)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	140 cm
Package 1 Width	38 cm
Package 1 Length	90.7 cm
Package 1 Weight	415.5 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Total lifecycle Carbon footprint	40 455 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	3 893 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	649 kg CO2 eq.
Carbon footprint of the installation phase [A5]	44 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	35 232 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	636 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Again

Repack and remanufacture	
Recyclability potential, in %	81
End of life manual availability	End of Life Information
Removable battery	Yes

Image of product / Alternate images

Alternative





